



Teil-Nr.		Abmessungen				
Standard "S"	Selbstsichernd "L"	Gewinde A Ø A	Gewinde B Ø B	Flankenscherfläche inch <sup>2</sup> (mm <sup>2</sup> )	C inch (mm)	C1 inch (mm)
KNCA0256J		2-56" UNJC-3B	8-32" UNC-3A	0,0157 (10,1)	0,12 (3,05)	0,088 (2,24)
KNCA0440J		4-40" UNJC-3B	10-32" UNF-2A	0,0302 (19,5)	0,17 (4,32)	0,125 (3,18)
	KNCAL0440J			0,0302 (19,5)		
KNC0632J		6-32" UNJC-3B	12-28" UNF-2A	0,0329 (21,2)	0,17 (4,32)	0,125 (3,18)
	KNCL0632J			0,0329 (21,2)		
KNCA0832J		8-32" UNJC-3B	1/4-28" UNF-2A	0,0669 (43,2)	0,22 (5,59)	0,175 (4,45)
	KNCAL0832J			0,0669 (43,2)		

Teil-Nr.	Einbaumaße				Handeinbauwerkzeug Teil-Nr.	Ausbaumaß	
	Ø D Kern-Ø inch	Ø E Senk-Ø inch	Gewinde F			Bohrung	
			Ø F	G min. inch (mm)		Ø inch (mm)	Tiefe inch (mm)
KNCA0256J	.134 <sup>+0,003</sup> -0,001	.166 <sup>+0,001</sup> -0,000	8-32 UNC-2B	0,140 (3,56)	TKNC02	0,113 (2,87)	1/16 (1,59)
KNCA0440J	.161 <sup>+0,003</sup> -0,001	.194 <sup>+0,001</sup> -0,000	10-32 UNF-2B	0,160 (4,06)	TKNC04	0,136 (3,45)	3/32 (2,38)
KNCAL0440J							
KNC0632J	.187 <sup>+0,003</sup> -0,001	.220 <sup>+0,001</sup> -0,000	12-28 UNF-2B	0,160 (4,06)	TKNC06	0,159 (4,04)	3/32 (2,38)
KNCL0632J							
KNCA0832J	.228 <sup>+0,003</sup> -0,001	.255 <sup>+0,001</sup> -0,000	1/4-28 UNF-2B	0,210 (5,33)	TKNC08	0,199 (5,05)	1/8 (3,18)
KNCAL0832J							